

Neutra Sul®

Professional Grade Oxidizer

PRO™
CHEMICALS

Protects against irregular coloring and smells in treated water.

Pro Neutra Sul® is formulated to neutralize pollutants in any water supply through oxidation. Neutra Sul should be used in place of Hydrogen Peroxide 7% solution to prevent the formation of colors, tastes, corrosion and scaling by pollution degradation. The stabilizer in Neutra Sul provides 5 times the shelf life of standard 7% hydrogen peroxide.

(Available in 1, 2.5 and 5 gallon sizes.)

Applications

Oxidation - Normal procedure for oxidizing a water supply is usually specified by the chemical feed pump manufacturer or supplier and depends on water conditions. There are many types, designs and methods of introducing Neutra Sul to the water supply. A normal method is to inject Neutra Sul directly into the water line with the use of a chemical feed pump. Dosage rates will vary. If unsure consult owner's manual.

Dosage - Proper dosage rates will vary depending on application. For oxidation of impurities, feed Neutra Sul until there are very few oxygen bubbles in treated water.



Benefits to the User	Technical Information	Part #	Size	Qty.
<ul style="list-style-type: none"> No odor Non flammable Decomposes into oxygen and water More powerful oxidant than chlorine and Potassium Permanganate 	<ul style="list-style-type: none"> Pro Neutra Sul is a clear, chemically stable, liquid formulated with 7% Hydrogen Peroxide. Neutra Sul should be properly vented, and stored away from sources of direct heat and combustible materials. Read relevant MSDS before handling product. Do not mix with other chemicals 	HP41N	1 gal.	4
		HP22N	2.5 gal	2
		HP05N	5 gal	1