

OnSite PRO Inc.

# FLOODSTOP™

**Stop Flood Damage Before It Really Starts!**

FloodStop FS1.00NPT is a point of use, leak detection and automatic water shut-off system designed for residential and commercial dwellings. The FS1.00NPT uses a Motorized Ball Valve to automatically shut off the water supply whenever your water heater leaks!

G.A. Murdock, Inc.  
1200 S Division Ave  
Madison, SD 57042

Phone 605.256.9632  
Fax 605.256.9682  
www.gamurdock.com



## Install in Minutes!

**Kit includes everything you need to protect your property:**

- 1" Motorized Ball Valve installed on cold water inlet.
- Water sensor is placed on the floor.
- Control Unit is mounted with screws or Velcro (included).
- Optional Power Sources: AC & (4) AA Batteries, or Batteries alone!

## Technical Specifications:

- UL listed class 2 wall adaptor, 115AC/9VDC
- UPC listed Full-Port Motorized Ball Valve: CNC machined.
- Motor operates at 6VDC.
- Signal Output: 1 Normally Open, 24 Volt / 2 amp rated
- Motorized Ball Valve: CNC machined with MIP X FIP.
- Rated 0-140 PSI. Max 250 PSI. Solid brass. AB1953, UPC, CUPC, NSF61 cert.
- Rated 32-212 degrees F
- Sensor: 1.25 X 7.5 inch, double sided. Additional sensors may be added in series.
- Alarm: Beeping with Mute button.

Water Heaters  
FS1.00NPT 1"



## FloodStop Product Lineup:

FS3/4H-90 Washing Machine (Hose Fittings)  
FS3/4H Washing Machine (Hose Fittings)  
FS3/4NPT Water Heater 3/4" (MIP X FIP)  
FS3/4C Water Heater (3/4" Compression)  
FS100NPT Water Heater (1.00" (MIP X FIP)  
FS125NPT Water Heater (1.25" (MIP X FIP)  
FS1/2NPT Water Heater 1/2" (MIP X FIP)  
FS3/8C Dishwasher, Toilet (3/8" Compression)  
FS3/8CD Sink (3/8" Compression)  
FS1/4C Ice Maker (1/4" Compression)